

SPECIFICATIONS

SPECIFICATIONS	TA 112		TA 116
	60' BOOM	90' BOOM	90' BOOM
Overall length	22' 7"	22' 7"	22' 8"
Overall height	9' 8"	12' 8"	13'
Under boom height (folded)	6' 4"	6' 4"	6' 5"
Underframe clearance	30"	30"	30"
Hitch to axle	15' 10"	15' 10"	15' 10"
Transport width	12'	12'	12'
Tongue weight – full	4,100 lbs.	4,500 lbs.	5,000 lbs.
Hubs	Large 8-bolt		10-bolt
Spindle diameter/material	3 3/4" (high-tensile steel)		3 3/4" (high-tensile steel)
Tank capacity	1200 gallon		1600 gallon
Rinse tank capacity	140 gallon		165 gallon
Sump containment tank	30 – 50 gallon		30 – 50 gallon
Tank thickness	1/4"		1/4"
Tank material	Polyethylene		Polyethylene
Hitch height	1' 10" – 2' 2"		1' 10" – 2' 2"

Alliance Product Group reserves the right to make changes in engineering, design and specifications at any time without notice or obligation.

TA 112 Tire Options/Specifications

SIZE	SURFACE AREA CONTACT
320/90 x 46 R-1	520 square inches
320/90 x 46 R-1W 146 LI	600 square inches
480/80 x 42 R-1 156 LI	730 square inches
380/90 x 46 R-1 8 Star	620 square inches

TA 116 Tire Options/Specifications

SIZE	SURFACE AREA CONTACT
380/90 x 46 R-1 8 Star	620 square inches
480/80 x 42 R-1 156 LI	730 square inches
320/90 x 50 R-1W 146 LI	650 square inches
380/90 x 46 R-1 8 Star (Duals)	1240 square inches
320/90 x 46 R-1W 146 LI (Duals)	1200 square inches
320/90 x 50 R-1W 156 LI (Duals)	1300 square inches
270/95 x 48 R-1 146 LI (Duals)	724 square inches

Infinitely adjustable axle — from 60" to 120" — accommodates a variety of wheel sizes and meets virtually any row crop spacing.