

SPECIFICATIONS

SPECIFICATIONS	TA 1200		TA 1600		TA 2400	
	90' BOOM		90' BOOM	120' BOOM	90' BOOM	132' BOOM
Tank capacity	1,200 gallons		1,600 gallons		2,400 gallons	
Rinse tank capacity	140 gallons		165 gallons		165 gallons	
Sump containment tank	30-50 gallons		30-50 gallons		30-50 gallons	
Tank thickness	1/4"		1/4"		1/4"	
Tank material	Polyethylene		Polyethylene		Polyethylene	
Overall length		22' 7"	22' 7"	25' 3"	22' 7"	25' 3"
Overall height		10' 3"	10' 3"	11' 10"	11' 10"	11' 10"
Under boom height (folded)		6' 4"	6' 4"	6' 4"	6' 4"	6' 4"
Underframe clearance		30"	30"	30"	30"	30"
Hitch to axle		15' 10"	15' 10"	18' 8"	18' 8"	18' 8"
Transport width		12'	12'	12'	12'	12'
Tongue weight — full		4,500 lbs.	5,000 lbs.	5,200 lbs.	6,250 lbs.	6,750 lbs.
Empty weight		8,420 lbs.	9,820 lbs.	12,480 lbs.	12,660 lbs.	15,320 lbs.
Water weight		9,996 lbs.	13,328 lbs.		19,992 lbs.	
Loaded sprayer weight		18,416 lbs.	23,148 lbs.	25,808 lbs.	32,625 lbs.	35,312 lbs.
Weight on tires		13,916 lbs.	18,148 lbs.	20,608 lbs.	26,402 lbs.	28,562 lbs.
Hubs		10-bolt	10-bolt		10-bolt	
Spindle diameter/material		3 3/4" (high-tensile steel)	3 3/4" (high-tensile steel)		3 3/4" (high-tensile steel)	
Hitch height		1' 10"—2' 2"	1' 10"—2' 2"		1' 10"—2' 2"	

Unverferth Manufacturing reserves the right to make changes in engineering, design and specifications at any time without notice or obligation.